

ARC630

MULTI PROCESS INVERTER (380/525V)

Product Code: 00026495

The ARC 630 is a reliable stick welder, designed for harsh working environments. With proven reliability in the rental industry, this unit offers both SMAW as well as GTAW with simplistic controls, arcsafe and multi-input voltage. The Arc 630 also offers arc controls such as hotstart and arcforce as well as remote capability and digital display. This machine boasts a 3 year parts and labour warranty and is generator compatible.





Output

t DC

Input

3

HASE 50 H OWER 380\

50 HZ/60 HZ 380V/525V

FEATURES

- SUITABLE FOR RUTILE AND BASIC ELETRODES
- ADJUSTABLE ARC FORCE AND HOT START
- WORK WITH GENERATOR (OPTIONAL)
- HEAVY DUTY CYCLE (UP TO 100%)
- VRD FEATURE (OPTIONAL)
- DIGITAL DISPLAY
- SUITABLE FOR LONG DISTANCE WELDING (100M)

OUTPUT RANGE

50 - 630 Amps

DIMENSIONS L X W X H

686 x 322 x 584 mm

DRY WEIGHT

58kg

APPLICATIONS

- · Shipbuilding and offshore engineering
- Industry plant construction
- · Maintainance and repair
- · Pipeline industry

WELDING PROCESS

SMAW / SCRATCH GTAW / GOUGING

SPECIFICATIONS

OI LOII IONI IONO	
ARC 630	
WELDING TYPE	SMAW / SCRATCH GTAW / GOUGING
INPUT VOLTAGE RANGE (VAC)	380 / 525
INPUT VOLTAGE RANGE SELECT (VAC)	AUTO-SELECT
INPUT CURRENT MAX (A)	52 / 38
PHASE INPUT & FREQUENCY	3 PH - 50/60 HZ
CURRENT ADJUSTMENT RANGE (A-DC)	50 - 630
DUTY CYCLE	630 A / 60%
DUTY CYCLE	480 A / 100%
FULL LOAD EFFICIENCY	89%
REQUIRED INPUT POWER (NETWORK)	51 KVA
REQUIRED INPUT POWER (GENERATED)(FULL CAP)	60 KVA
OPEN CIRCUIT VOLTAGE (OCV) (MMA)	15 / 80 VDC
ARC-SAFE FACILITY (VRD)	ON / OFF (SELECT)
PROTECTION CLASS	IP23S
WORKING TEMPERATURE (°C)	-10-+40
DRY WEIGHT (KG)	58
SIZE (CM) L X W X H	69 X 32 X 55
INPUT CIRCUIT BREAKER (MACHINE)	80 A / 3PH
INPUT POWER CABLE BLACK (MM2)	4C X 6 X 3M
REQ INPUT POWER CABLE EXT (MM2)	4C X 25 X 20 M



ADDITIONAL ITEMS

UNIARC PROGRIP 26V TIG TORCH





REMOTE CONTROL





GOUGING TORCH



TROLLEY



FLOWMETER & GAS HOSE

Description

Flowmeter & Gas hose - Please specify gas as well as length of Gashose





ELECTRODE HOLDER

Description

Earthclamp and cables - Please specify length and amperage required







WELDING HELMET

Code	Model	Description
36944	ADF815S	TM16 BLUE TM16-ADF815S B
36945	ADF815S	TM16 BLACK AND WHITE TM16-ADF815S BW
36946	ADF725S	M17 GLOSS BLACK TM17-ADF725S B
36947	ADF725S	TM17 RED TM17-ADF725S R
40961	TM1000	TM1000 BLACK FLIP FRONT AUTO DARKENIG HELMET
16221	WC715	UNIARC WELDCREW AUTO DARKENIG HELMET
41826		NECK PROTECTION TECMEN NP003
41827		HP011-B EXTENDED HEAD PROTECTION TECMEN HELMETS













