

SPECIFICATIONS

X-CUT Roughneck	
INPUT VOLTAGE	230V 50/60HZ
POWER SUPPLY FREQUENCY	50HZ
RATED POWER	500-1000W
EFFECTIVE CUTTING WIDTH (MM) (X AXIS)	1500
EFFECTIVE CUTTING LENGTH (MM) (Y AXIS) (Could be extended as per customer demand)	3000
PROCESSES	PLASMA CUTTING, OXYFUEL CUTTING
CUTTING MODE	GAS / PLASMA CUTTING
MOTOR STYLE	STEP MOTOR
DRIVE MODE	SINGLE-SIDE
GAS CUTTING THICKNESS	6-100MM
PLASMA CUTTING THICKNESS	0.5MM - 40MM DEPENDING ON PLASMA POWERSOURCE
CUTTING SPEED	10-3000MM/MIN
WORKING PRECISION	±0.2MM/METER
CUTTING GAS	OXYGEN + ACETYLENE/ PROPANE
GAS PRESSURE	OXYGEN: ≤1MPA FUEL: ≤0.1MPA
TORCH HEIGHT CONTROL MODE	MOTOR DRIVE TORCH HEIGHT CONTROL
DISPLAY SCREEN	LCD COLOR SCREEN
NESTING SOFTWARE	FASTCAM

Safety Gear

Product Code	Model	Description
43873	TM-S4	FACE SHIELD FOR GRINDING AND PLASMA CUTTING





RECOMMENDED POWER SOURCE



CUT451_{PFC} **PLASMA CUTTER INVERTER (380V)**

Product Codes: 00037184

The CUT451 PFC plasma cutter is a ready to go single phase plasma inverter, designed for the job site. This pilotarc system offers quality cuts, fast cutting speeds and simple operation, combined with the powerfull CP70 pilotarc torch. Whether cutting gratings or plate, the pilotarc system keeps the arc stable for effortless cutting. Just add your external air supply and you are ready to cut. This unit also offers 2T/4T functionality, as well as CNC interface as standard for integration onto your plasma table.

CUT 451 PFC	
INPUT VOLTAGE	1-PH AC230V(160-265V) 50/60HZ
OCV	DC280V
OUTPUT CURRENT	10A-45A
DUTY CYCLE(UNDER 40C°)	35%
QUICK CONNECTOR	16-25B

Cutting Thickness

Quality cuts: 12 mm Severance cuts: 20 mm

Material

Carbon steel / Stainless steel / Aluminium

Choose your cutting torch

Product	Code	Description
40511		MINI TORCH 8M CX NIARC 03632MX-RT
40509		LUGS FOR TRIGGER UNIARC 10004659



Accessories

Product	Code	Description
40497	MALE PLUGS FOR VOLTAGE HEIGHT SENSING	\ /
		10059739
40498	CPM70 70A 8M CX OHMIC CEN 1-9-3-6 UNIAR	C 03632CX-RT



CUT803

PLASMA CUTTER INVERTER (380V)

Product Codes: 00037185

The CUT803 plasma cutter is a ready to go industrial plasma inverter, designed for the job site or workshop. This pilotarc system offers quality cuts, fast cutting speeds and simple operation, combined with the powerfull CP125 pilotarc torch. Whether cutting gratings or plate, the pilotarc system keeps the arc stable for effortless cutting. Just add your external air supply and you are ready to cut. This unit also offers 2T/4T functionality, as well as CNC interface as standard for integration onto your plasma table.

CUT 803	
INPUT VOLTAGE	3PH- AC380V±15% 50/60HZ
OCV	DC310V
OUTPUT VOLTAGE	88V-112V
OUTPUT CURRENT	20A-80A
DUTY CIRCLE	40%
QUICK CONNECTOR	16-25/EURO

Cutting Thickness

Quality cuts: 20 mm Severance cuts: 30 mm

Carbon steel / Stainless steel / Aluminium / Copper / Cast iron

Choose your cutting torch

Product	Code	Description
40521		M CX OHMIC CEN ARC 03732CX-RT
42249	CPM125 OHMIC W 1-9-3-6 UNIA	I/RACK 15M 125A RC 03737CXR-RT



Accessories

Product Code Descrip	
40497	MALE PLUGS FOR VOLTAGE HEIGHT SENSING (CNC) UNIARC 10059739
40498	CPM70 70A 8M CX OHMIC CEN 1-9-3-6 UNIARC 03632CX-RT



CUT125PRO **PLASMA CUTTER**

Product Codes: 00043416

The CUT 125 PRO is an industrial plasma cutter designed for serious cutting applications. It has a 100% duty cycle at 125 Amps making ideal for production cuts by hand or on an automated system or table. The marking mode also makes it ideal to mark your parts for traceability

CUT 125 PR0		
Work mode		Cutting/Gouging
Power Supply		400 V - 3 ph, 50/60 Hz
Fuse		63 A
Current range		20-125 A
Duty cycle EN 60974-1	(40°C)	125 A @ 100%
Air pressure		5 > 9 bar
Recommended cut (Clean cut)	Steel Stainless steel / Alu	40 40
Maximum cut (Separation)	Steel Stainless steel / Alu	57 57
Piercing	Steel Stainless steel / Alu	25 25
Gouging	Withdrawal rate	12 kg/h
IP		IP 23
Protected & compatible	e power generator (+/-1	5 %) 30 kW

Material

Alloy steel / Stainless steel / Copper / Aluminum and other non-ferrous metals

Choose your cutting torch

Product Code	e Description
43433	CPM160 160AMP 180DEG MACHINE TORCH OHMIC 8M EURO CONNECTOR
43434	CPM160 160AMP 180DEG MACHINE TORCH OHMIC 12M EURO CONNECTOR



SIMILAR PRODUCTS **UNIARC XCUT ARTISAN**



UNIARC XCUT PROFESSIONAL



UNIARC XCUT PIPE



COPYRIGHT® 2024 RENTTECH SOUTH AFRICA

Rentech SA reserves the right to make changes to specifications of products described at any time without notice and without obligation to notify any person of such changes. Weight and dimensions are approximate. Names or products not mentioned may be registered trademarks or trademarks of the company.

BLOEMFONTEIN +2751 430 8310/14 CAPE TOWN +2721 511 1160 DURBAN +2731 902 7595/+2787 158 5819 EAST LONDON +2743 736 6440 EMALAHLENI (WITBANK) +2713 697 3030 KATHU +2783 382 6876 LEPHALALE (ELLISRAS) +2714 763 4150 PORT ELIZABETH +2741 484 4624/7

RICHARDS BAY +2735 751 1965 RUSTENBURG +2714 592 1667/9 SASOLBURG +2716 971 2868 SECUNDA +2717 631 3815













